

ZL-S2020/2021

2U/19-inch standard server chassis,
supports up to E-ATX motherboards



技术参数

| | |
|------|----------------------------------------------------------------------------------------------------------------|
| 机箱形态 | 机架式 |
| 机箱高度 | 2U |
| 适应主板 | E-ATX/ATX/Micro-ATX及以下 |
| 背板 | 12Gb/s直连背板 + U.2背板 |
| 磁盘位 | 支持S6PI0, 兼容SAS3.0/SATA3.0/U.2硬盘, 标配支持8块3.5" (或2.5")及4块U.2 3.5" (或2.5")热插拔硬盘位, 可选配2块2.5"内置非热插拔扩展位和后置2块2.5"热插拔盘位 |
| 硬盘防震 | 硬盘架采用EMI弹片设计, 独有防震风扇设计, 降低风扇与硬盘间共振, 不影响硬盘I/O速度 |
| 系统风扇 | 支持智能温控, 标配3个8038热插拔风扇, 最大支持4个8038热插拔风扇 |
| 扩展卡位 | 7个半高的PCIe扩展卡位, 可选配2个横转全高扩展卡位 + 一个半高横转扩展卡 |
| 前板控制 | 2个USB 2.0, 1个开关键, 1个重启键, 1个UID, 1个硬盘指示灯, 1个系统故障灯, 2个网络指示灯 |
| 滑轨 | 选配 |
| 产品材质 | 进口SGCC(镀锌钢板) |
| 机箱尺寸 | 670 x 450 x 88mm |
| 机箱毛重 | 10.8KG |
| 包装尺寸 | 880 x 580 x 220mm |

Features

- 主板最大支持E-ATX (12"x13")及以下规格
- 12Gb/s直连背板+U.2背板
- 支持单电或者1+1冗余电源
- 智能温控, 最多支持4x 8038热插拔风扇
- 可选横插全高双位卡

Technical Parameter

| | |
|------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Chassis style | rack type |
| Chassis height | 2U |
| Supported Motherboards | E-ATX/ATX/Micro-ATX and below |
| backplane | 12Gb/s direct connection backplane U.2 backplane |
| Disk slot | Supports S6PI0, compatible with SAS3.0/SATA3.0/U.2 hard drives, standard supports 8 3.5" (or 2.5") and 4 U.2 3.5" (or 2.5") hot swappable hard drive slots, optional 2 2.5" built-in non hot swappable expansion slots and 2 rear 2.5" hot swappable disk slots |
| Hard drive shockproof | The hard drive rack adopts EMI shrapnel design and a unique shock-absorbing fan design to reduce resonance between the fan and the hard drive, without affecting the I/O speed of the hard drive |
| System fan | Supports intelligent temperature control, comes standard with 3 8038 hot swappable fans, and can support up to 4 8038 hot swappable fans |
| Expansion slot | 7 and a half height PCIe expansion card slots, optional with 2 horizontal full height expansion cards and 1 half height horizontal expansion card |
| Front panel control | 2 USB 2.0, 1 power button, 1 restart button, 1 UID, 1 hard drive indicator light, 1 system fault light, 2 network indicator lights |
| Sliding rail | Optional |
| Product Material | Imported SGCC (galvanized steel sheet) |
| Case size | 670 x 450 x 88mm |
| Case gross weight | 10.8KG |
| Package dimensions | 880 x 580 x 220mm |

