

ZL-S4030/4031

4U/19-inch standard server chassis supports up to ATX motherboards



Features

- 主板最大支持ATX及以下规格
- 12Gb/s直连背板，兼容SAS/SATA硬盘
- 支持ATX电源
- 智能温控，最多支持4x8025风扇,2x6025风扇

技术参数

| | |
|------|---|
| 机箱形态 | 机架式 |
| 机箱高度 | 4U |
| 适应主板 | ATX/Micro-ATX及以下 |
| 背板 | 12Gb/s直连背板 |
| 磁盘位 | 标配支持8块3.5/2.5热插拔硬盘位 |
| 硬盘防震 | 硬盘架采用EMI弹片设计 |
| 系统风扇 | 支持智能温控，标配3个8025风扇，最多支持4x8025风扇,后置2x6025风扇 |
| 扩展卡位 | 5个全高的PCIe扩展卡位 |
| 前板控制 | 2个USB 2.0, 1个开关键, 1个重启键, 1个UID, 1个硬盘指示灯, 1个系统故障灯, 1个网络指示灯 |
| 滑轨 | 选配 |
| 产品材质 | 进口SGCC(镀锌钢板) |
| 机箱尺寸 | 362 x 438 x 162mm |
| 机箱毛重 | 12kg |
| 包装尺寸 | 477 x 553 x 292mm |

Technical Parameter

| | |
|------------------------|--|
| Chassis style | rack type |
| Chassis height | 4U |
| Supported Motherboards | ATX/Micro ATX and below |
| backplane | 12Gb/s direct connection backplane |
| Disk slot | Standard configuration supports 4 3.5/2.5 hot swappable hard drive slots |
| Hard drive shockproof | The hard drive rack adopts EMI shrapnel design |
| System fan | Supports intelligent temperature control, comes standard with 3 8025 fans, supports up to 4x8025 fans, and rear 2x6025 fans |
| Expansion slot | 5 full height PCIe expansion card slots |
| Front panel control | 2 USB 2.0, 1 power button, 1 restart button, 1 UID, 1 hard disk indicator light, 1 system fault light, 1 network indicator light |
| slide rail | optional |
| Product Material | Imported SGCC (galvanized steel sheet) |
| Case size | 362 x 438 x 162mm |
| Case gross weight | 12kg |
| Package dimensions | 477 x 553 x 292mm |

